

## PRODUCT CONVEYORS



- A Wide Variety of Conveyor Designs Including Full or Partial Width with Flush Grid, Raised Rib, or Flat Top, Side Flexing Full or Partial Width Plastic Belt Conveyors, and Multiflex Wire Belt Conveyors


### FEATURES & BENEFITS

#### SERIES 900, FLUSH GRID


Full or Partial Width Plastic Belt Conveyor, Raised Ribs, or Flat Top




- Aluminum 6061-T6, low or high belting in frame
- Intralox Series 900:
  - Raised ribs belt construction available in grey or white polypropylene or in blue Acetal
  - Flush grid and flat top belt construction available in grey or white polypropylene in blue Acetal or in brown heat resistant nylon



Flush Grid



Flat Top




Raised Ribs

#### SERIES 2200, FULL WIDTH

Side Flexing Plastic Belt Conveyor



- Aluminum 6061-T6, low or high belting in frame
- Continuous path conveyors reduce the number of drives required on a layout
- Intralox Series 2200:
  - Flush grid radius belt construction
  - Grey or white polypropylene
  - 12" (305 mm), 14" (356 mm), 20" (508 mm), 22" (559 mm) and 26" (660 mm) wide belt available



Flush Grid Radius

#### MULTIFLEX WIRE BELT

Straights and Turns Wire Belt Conveyor



- Flat anodized aluminum side frame
- Stainless steel wire belting
- Continuous UHMW - Nylatron wear strips

### MECHANICAL FEATURES

#### SERIES 900, FLUSH GRID

Full or Partial Width Plastic Belt Conveyor, Raised Ribs, or Flat Top



- 14 1/4" (362 mm), 22 1/4" (565 mm), 26 1/4" (666 mm) and 30 1/4" (768 mm) outside frame, other widths available on request
- All belts are available from 6" (152 mm) to 42" (1067 mm) in 1" (25mm) increments
- Low or high belting in frame. Low: 1/4" x 7" (6mm x 178 mm), High: 1/4" x 10" (6mm x 254 mm)
- Motor and reducer shaft mounted, other mountings available on request (side drive, drive over, drive under)
- Standard reducer: Sew Eurodrive (Optional: Doerr, Boston, Ohio, Sterling, Tigear, Nord, Browning)
- Standard motor: Sew Eurodrive (Optional: US Motor, Leeson, Baldor, Reliance, Nord)
- Standard bearings: Dodge (Optional: Sealmaster, Dodge, SKF)

#### SERIES 2200, FULL WIDTH

Side Flexing Plastic Belt Conveyor



- 14 1/4" (362 mm), 16 1/4" (412 mm), 22 1/4" (565 mm), 24 1/4" (616 mm) and 28 1/4" (717 mm) outside frame, other widths available on request
- 12" (305 mm), 14" (356 mm), 20" (508 mm), 22" (559 mm), and 26" (660 mm) full width belt, other widths available on request
- Low or high belting in frame. Low: 1/4" x 7" (6mm x 178 mm), High: 1/4" x 10" (6mm x 254 mm)
- Motor and reducer shaft mounted, other mountings available on request (side drive, drive over, drive under)
- Standard reducer: Sew Eurodrive (Optional: Doerr, Boston, Ohio, Sterling, Tigear, Nord, Browning)
- Standard motor: Sew Eurodrive (Optional: US Motor, Leeson, Baldor, Reliance, Nord)
- Standard bearings: Dodge (Optional: Sealmaster, Dodge, SKF)

#### MULTIFLEX WIRE BELT

Straights and Turns Wire Belt Conveyor



- Motor and reducer shaft mounted, other mountings available on request (side drive, drive over, drive under)
- Standard reducer: Sew Eurodrive (Optional: Doerr, Boston, Ohio, Sterling, Tigear, Nord, Browning)
- Standard motor: Sew Eurodrive (Optional: US Motor, Leeson, Baldor, Reliance, Nord)
- Standard bearings: Dodge (Optional: Sealmaster, SKF)

### OPTIONS

#### SERIES 900, FLUSH GRID

Full or Partial Width Plastic Belt Conveyor, Raised Ribs, or Flat Top



- Nose down, nose up
- Transfer rollers
- Adjustable guides (funnel type)
- Anti-static device (when required)

#### SERIES 2200, FULL WIDTH

Side Flexing Plastic Belt Conveyor



- Nose down, nose up
- Transfer rollers
- Adjustable guides (funnel and straight type - manually or screw adjustable)
- Anti-static device (when required)

**Headquarters:**  
2115 W. Laburnum Ave.  
Richmond, Virginia 23227  
Tel: 1-800-225-3771  
or 1-804-355-7961  
Fax: 1-804-342-9724  
[sales@amfbakery.com](mailto:sales@amfbakery.com)

**Europe Office:**  
West Park Ring Road  
Leeds LS16 6QQ  
England  
Tel: 44-1132-787110  
Fax: 44-1132-741415  
[sales-europe@amfbakery.com](mailto:sales-europe@amfbakery.com)

**Asia Office:**  
Room 15-2, A-Building  
Thunis Dev. Building  
No.11 Hui Xin East St.  
Chaoyang District  
Beijing, China 100029  
Tel: 86-10-64823613  
Fax: 86-10-64934259  
[sales-asia@amfbakery.com](mailto:sales-asia@amfbakery.com)

FOR MORE INFORMATION PLEASE CALL YOUR ACCOUNT MANAGER OR

**1-800-BAKERS-1**  
**www.amfbakery.com**